

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
4 March 2004 (04.03.2004)

PCT

(10) International Publication Number
WO 2004/018170 A1

- (51) International Patent Classification⁷: **B27B 17/00**, F02F 7/00
- (74) Agent: **LILJEGREN, Fredrik**; AB Electrolux (publ), Group Intellectual Property, S-105 45 Stockholm (SE).
- (21) International Application Number: **PCT/SE2003/001285**
- (22) International Filing Date: 18 August 2003 (18.08.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0202495-8 21 August 2002 (21.08.2002) SE
- (71) Applicant (for all designated States except US): **AKTIEBOLAGET ELECTROLUX [SE/SE]**; S-105 45 Stockholm (SE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **OSSIANSOON, Mattias [SE/SE]**; Göransbergsvägen 12, S-561 38 Huskvarna (SE). **BJÖRKMAN, Peter [SE/SE]**; Furulidsgatan 1, S-578 38 Aneby (SE). **GANHAMMAR, Mikael [SE/SE]**; Sörängsvägen 22, S-561 46 Huskvarna (SE). **STEGEMYR, Erik [SE/SE]**; Vegatan 8, S-553 32 Jönköping (SE).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DEVICE FOR A PORTABLE TOOL



(57) Abstract: The claimed invention relates to an engine powered portable tool comprising a working tool placed on a working tool carrier clamped to a tool casing (10). In order to increase the strength in the section where the working tool carrier is clamped to the tool casing (10) is the working tool carrier clamped to a protruding part (20) of the crankcase (12) provided with a component (16) embedded in the crankcase (12) wall when the crankcase (12) is casted. The component (16) is made of a material with higher E-module than the material in the rest of the crankcase (12).

Device for a portable tool

The invention relates to a new solution in order to increase the stiffness in the
5 connection between the working tool carrier, where the working tool or tools are placed,
and the body of a portable engine powered tool.

Portable handheld tools, like for example chain saws and power cutters, are used for
different kinds of work in forestry and construction activities. The tools are available in
10 several different embodiments adapted to meet the requirements of the work that it is
supposed to do and also to meet the operators needs and physique.

The increased use of these types of tools makes it important that the tools are easy for
the operator to handle and not subject the operator that is working long shifts with the
15 tool to higher loads and risks than necessary.

The load that the operator is subjected to is a combination of the design of the tool and
the actual weight of the tool. The weight of the tool is reduced either by an optimized
design of the different components that are included in the tool or by making the
20 components in materials with a low density. Both alternatives are normally used.

Many of the materials that is usable when it comes to efficient production, good shaping
possibilities and low weight are, however, comparatively weak. This means that their E-
module is low. Components made of these weak materials will consequently result in a
25 weak tool, which will have a bad influence on the performance of the tool as well as
increase the risk for breakdowns.

There are however materials with a low density, for example aluminum and
magnesium, which have an E-module that is high enough to make the different
30 components strong enough to handle the loads that they are subjected to. The cost for
tools comprising components made of these materials is unfortunately very high since
both the material and the manufacturing of components in these materials is more
complicated because more advanced production methods are required.

One part of the tool that is subjected to high loads when the tool is used is the place where the working tool carrier is attached to the tool casing. This section is subjected to both bending and torsional moment when the tool is used. A high stiffness in this section is therefore required in order to ensure a high performance of the tool. There is a
5 direct relationship between the stiffness in the section where the working tool carrier is attached to the tool casing and the final result of the performed work. Also the reliability and the safety for the operator are affected by the stiffness in this section.

The section where the working tool carrier is attached to the tool casing is a critical
10 section on tools like chain saws and power cutters, especially on smaller and simpler models that have several components made of plastic materials in order to keep the price and the weight of the tool at a low level.

In DE4134640C1 is a solution that increases the stiffness of the section where the guide
15 bar is attached to the tool casing illustrated. The crankcase as well as the surface on the casing that the guide bar is aligning is made of a plastic material. In order to increase the stiffness in this section is one component made of a material with higher E-module than the plastic material in the crankcase. The component is placed so that one end of the component is in contact with the opposite side of the plastic surface that the guide
20 bar is aligning on the casing while the other end of the component is secured in the crankcase. The guide bar is clamped to the casing by two bolts extending in perpendicular direction from the plastic surface on the casing that the guide bar aligns. The two bolts extend through the plastic detail and is secured in the component with higher E-module to increase the stiffness in the section where the guide bar is attached to
25 the tool casing to improve the performance of the tool.

The solution described above, however, has several drawbacks. The guide bar aligns a surface made of a weak plastic material with a low E-module which means that there will be movement in the section where the guide bar is attached to the tool casing when
30 the working tool carrier is subjected to high loads during use. The solution described in DE4134640C1 also includes several different components that will make the mounting of the tool time consuming and more complicated. Furthermore, the use of a separate component for increasing the stiffness in the section where the guide bar is attached to

the tool casing takes a lot of space since the total height of the crankcase and the component is big.

- 5 In this application is a new solution for the section where the working tool carrier is attached to the tool casing illustrated. The new solution increases the stiffness in the section where the working tool carrier is attached to the tool casing and reduces the space that is needed. The new solution also keeps the cost for material and manufacturing at a reasonable level without increasing the total weight of the tool.
- 10 This new solution, which is further defined in the claims, for tools provided with a crankcase in a material with a low E-module, for example a plastic material, means that a reinforcement component is embedded in the crankcase at the same time as the crankcase is casted.
- 15 The reinforcement component could have different shapes but will always extend between the crankcase and the section where the working tool carrier is attached to the tool casing. In order to achieve maximum stiffness in the section is the embedded reinforcement placed so that it creates a part or the entire surface on the tool casing that the working tool carrier aligns. The surface of the embedded reinforcement component
- 20 is not covered by the material that the rest of the crankcase is made of so that the reinforcement component is in direct contact with the surface of the working tool carrier. The reinforcement component is made of a material with an E-module higher than the material in the crankcase.
- 25 The new solution makes the working tool carrier align a surface with a high E-module, instead of like the solution described in DE4134640C1 where the guide bar is aligning a plastic surface with a low E-module which will cause bigger movements between the guide bar and the tool casing.
- 30 The working tool carrier is clamped to the surface on the tool casing by bolts. The working tool carrier is thereby fastened to the tool via the embedded reinforcement component. This solution increases the stiffness in the section where the working tool carrier is attached to the tool casing considerably since the intermediate layer of a material with low E-module is eliminated.

The new solution described above also reduces the numbers of components in the tool. The manufacturing and mounting process of the tool is thereby facilitated. The reduced number of components also reduces the total weight of the tool, which is favorable for this type of tools since the operator is carrying the tool and a lower weight reduces the loads on the operator.

The new solution with an embedded reinforcement in the weaker crankcase not only reduces the number of components and it also reduces the total size of the crankcase and related components. This means that it is possible to reduce the size of the tool, which makes it easier for the operator to handle and use the tool.

One embodiment of the claimed invention is illustrated in the drawings:

- Figure 1. Illustrates a side view of the tool casing for a chain saw.
- Figure 2. Illustrates a cross section along line II-II through the tool casing in figure 1.
- Figure 3. Illustrates a perspective view of the reinforcement component before it is embedded in the crankcase.
- Figure 4. Illustrates the reinforcement component seen from above.

In figure 1 is a tool casing 10 for a chain saw illustrated. The tool casing 10 includes a number of different parts like for example a surface 11 that a working tool carrier will be clamped to. If the tool is a chain saw, the working tool carrier will be a not illustrated guide bar. One side of the crankcase 12 is illustrated to the left of the surface 11. The crankcase 12 has an opening 13 for a not illustrated crankshaft that will drive the working tool extending from the working tool carrier. Above the crankcase 12 is a cylinder 14 for the combustion engine placed.

Figure 2 illustrates a cross section through the tool casing 10 in figure 1. Two bolts 15 for clamping the working tool carrier to the tool casing 10 extend from the surface 11 that the working tool carrier aligns. In this cross section through the crankcase 12 is a component 16 used for reinforcing the section where the working tool carrier is attached

to the tool casing 10. The component 16 is embedded in the crankcase 12 walls when the crankcase 12 is casted in a mould and placed so that it extends between the crankcase 12 and the surface 11 that the working tool carrier aligns. The shape of the component 16 makes it possible to fasten the bolts 15 for clamping the working tool carrier to the surface 11. The bolts are secured directly in the component 16 or with suitable nuts placed in recesses in the component 16.

The crankcase 12 normally comprises several different parts and the crankcase 12 is divided along a line through the centre of the not illustrated crankshaft to facilitate the manufacturing and mounting. The different parts of the crankcase 12 are held together by screws passing through the four holes 17 in the lower part of the crankcase 12 and the corresponding holes in the cylinder 14. The holes 17 for the screws also extend through the component 16 used for reinforcing the structure that are placed in one part of the crankcase 12 which will increase the stiffness in the crankcase 12, the surface 11 and the working tool carrier since the component 16 is held in the right position in relation to the different parts of the crankcase 12.

The crankcase 12 is made of a material with a lower E-module than the component 16. In order to increase the stiffness in the section where the working tool carrier is attached to the tool casing 10 further is the protruding part 20 of the component 16 that creates the surface 11 not covered by the material that the rest of the crankcase 12 are made of so that a section 18 is generated. This makes the working tool carrier align the component 16 via the section 18 with higher E-module than the rest of the crankcase 12. This increases the stiffness.

25

In figure 3 is a perspective view of the component 16 used for reinforcing the section where the working tool carrier is attached to the tool casing. The component 16 is shaped to fit into the lower part of the crankcase 12. This means that the component for example is provided with recesses 19 for bearings for the not illustrated crankshaft. Selected parts of the component 16 are not embedded by the material with lower E-module during the casting of the crankcase 12 since this will improve the result of the crankcase 12 when it is finally put together. The screws that keep the different parts of the crankcase 12 together extend through holes 17 in the component 16 to secure the component 16 in relation to the different parts of the crankcase 12. The protruding part

20 of the component 16 is provided with two recesses 21 where the two bolts 15 for clamping the working tool carrier to the tool casing is fastened and the section 18 that the working tool carrier aligns.

- 5 Figure 4 illustrates the component 16 seen from above. In this figure is the component 16, opposite the other figures, separated from the rest of the tool casing. The protruding part 20 and the section 18 that aligns the working tool carrier is here clearly illustrated.

Claims:

1. Engine powered portable tool comprising a working tool placed on a working tool carrier clamped to a tool casing (10) comprising at least a crankcase (12),
5 **characterized in** that the working tool carrier is clamped to a protruding part (20) of the crankcase (12) provided with a component (16) embedded in the crankcase 12 wall when the crankcase (12) is casted, said component (16) is made of a material with higher E-module than the material in the rest of the crankcase (12).
- 10 2. Engine powered portable tool according to claim 1, **characterized in** that the component (16) is shaped so that it is a part of the crankcase (12) and extend between the crankcase (12) and the section where the working tool carrier is clamped to the tool casing (10).
- 15 3. Engine powered portable tool according to claim 1 or 2, **characterized in** that the component (16) is made of aluminum, magnesium or some type of metal composition.
- 20 4. Engine powered portable tool according to claim 1, 2 or 3, **characterized in** that the crankcase (12) is made of a plastic material or a material with low density.
5. Engine powered portable tool according to any of the previous claims, **characterized in** that the protruding part (20) is provided with a surface (11)
25 that the work tool carrier is clamped to.
6. Engine powered portable tool according to claim 5, **characterized in** that the component (16) is shaped and placed so that a section (18) of the component (16) not is covered by the material that the rest of the crankcase (12) is made of
30 so that the section (18) is a part of or the entire surface (12) that the working tool carrier aligns.

7. Engine powered portable tool according to claim 5, **characterized in** that the working tool carrier is clamped to the tool casing (10) by one or more bolts (15) secured in the component (16) or thereto related nuts.
- 5 8. Engine powered portable tool according to any of the previous claims, **characterized in** that the component (16) is placed in such a way in the crankcase (12) that at least one of the screws that keep the different parts of the crankcase (12) together also extend through the component (16).




FIG. 1




FIG. 2




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 03/01285

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B27B 17/00, F02F 7/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B27B, F02F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6363618 B1 (BERNHARD DÜRR), 2 April 2002 (02.04.02), column 3, line 15 - line 57, abstract --	1-8
X	US 5243764 A (DIETER WIELAND), 14 Sept 1993 (14.09.93), column 4, line 4 - line 11 --	1-8
X	US 5029393 A (AKIRA NAGASHIMA ET AL), 9 July 1991 (09.07.91), column 2, line 24 - line 39 -- -----	1-8

☐

Further documents are listed in the continuation of Box C.

☒

See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

17 November 2003

Date of mailing of the international search report

20-11-2003

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Linda Melin/MP

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

06/09/03

International application No.

PCT/SE 03/01285

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
US	6363618	B1	02/04/02	DE	19909704 A	07/09/00
				JP	2000254901 A	19/09/00

US	5243764	A	14/09/93	DE	4134640 C	06/05/93
				JP	3107659 B	13/11/00
				JP	5212701 A	24/08/93

US	5029393	A	09/07/91	DE	4011929 A,C	18/10/90
				JP	2222669 A	05/09/90
				JP	2744628 B	28/04/98
				SE	505084 C	23/06/97
				SE	9001327 A	16/10/90
